

SPECIFICATION SHEET

Oct-2022 GCP Industrial Products

Name FDA Grade Silicone Sheet Rubber

Code 81-SIL-FDA-SS

1. DIMENSIONS AND APPEARANCE

Thickness in 1/32, 1/16, 3/32, 1/8, 1/4, 3/8, 1/2, custom thicknesses available

 Typical length
 ft
 50 - 100

 Typical width
 in
 36, 48, 60, 72

Surface finishing Smooth finish, both sides

Color Red/orange, translucent, black, others available

2. PHYSICAL PROPERTIES

Hardness Tensile strength, min Elongation, min Tear strength (Die C), min Specific gravity, typical Low working temp	Shore A psi % ppi g/cm ³ °F	40 ± 5 950 400 90 1.13 -80	50 ± 5 1100 350 100 1.15 -80	60 ± 5 1100 280 100 1.18 -80	70 ± 5 1000 200 100 1.21 -80	80 ± 5 1000 200 95 1.25 -80	ASTM D2240 ASTM D412 ASTM D412 ASTM D624
High working temp	°F	450	450	450	450	450	

81-SIL-FDA-SS meets FDA regulation 21 CFR 177.2600 for rubber articles intended for repeated use.

3. TOLERANCES

TARGET THICKNESS, in (mm)	MINIMUM, mm	MAXIMUM, mm
1/32 (0.8)	0.50	1.10
1/16 (1.6)	1.30	1.90
3/32 (2.4)	2.00	2.80
1/8 (3.2)	2.70	3.70
1/4 (6.4)	5.90	6.90
3/8 (9.5)	8.70	10.30
1/2 (12.7)	11.90	13.50

Width tolerance in (mm) +0.787 / -0 (+20 / -0)**Length tolerance** in (mm) +7.87 / -0 (+200 / -0)